

EXCEEDS INDOOR AIR QUALITY STANDARDS FOR VOCs USING  
**EPA TEST METHOD 8260B**

SW-846 Test Method 8260B: Volatile Organic Compounds by Gas Chromatography/Mass Spectrometry (GC/MS)



PRODUCTS

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| <b>3100 Sheet Goods Adhesive</b>  | <b>9500 VCT Adhesive</b>          |
| <b>3500 Sheet Goods Adhesive</b>  | <b>9500 Platinum VCT Adhesive</b> |
| <b>6100 Carpet Pad Adhesive</b>   | <b>ESD 1005 Adhesive</b>          |
| <b>6200 Carpet Tile Adhesive</b>  | <b>FRP Adhesive</b>               |
| <b>6500 LVT Adhesive</b>          | <b>Wall Tile Adhesive</b>         |
| <b>6500 Platinum LVT Adhesive</b> | <b>RugLock</b>                    |

**Contain 0.0 g/mL VOCs**

This method determines most volatile organic compounds with boiling points below 200°C by gas chromatography/mass spectrometry (GC/MS). Method 8260 is used to determine volatile organic compounds in a variety of solid waste matrices.



5959 Shallowford Rd. Suite 405  
Chattanooga, TN 37421

423.305.5161

[www.spraylock.com](http://www.spraylock.com)

